

Your asphalt or bitmac surface will be damaged:

1. If any of the following type of liquids are spilled on to it:
 - petrol (e.g., from leaking vehicle fuel tanks, or when filling petrol driven lawnmowers)
 - diesel or heating oil
 - kerosene (paraffin)
 - engine or hydraulic oil
 - paint or paint thinners, e.g., white spirit
 - light petroleum distillates, e.g., lighter fluid, WD40
2. If exposed to excessive heat, from, for example:
 - bonfires
 - weed flame guns.
3. By moss, weed or algal growth, particularly in damp shaded areas.
4. If cement or concrete is mixed or spilled onto it.
5. By applying power steering while your vehicle is stationary.
6. If excessive loads are applied, e.g., parking HGV vehicles on a surface constructed for light duty (i.e., car parking on a driveway); motor bike stand or caravan jockey wheel indentation (particularly in warm weather).
7. If accessed by construction plant of any type, e.g., mini-diggers, JCBs etc. Surface may also be permanently marked if delivered soil or stones are dumped directly onto it.

Care and maintenance:

1. Cleaning – brush and hose down with water when required.
2. High pressure washers can damage the surface and are not recommended.
3. Other than mild, well diluted detergent, cleaning agents of any kind are not recommended.
4. Check the manufacturer's product instructions for any proposed moss or weed treatment to ensure that is suitable for use on asphalt or bitmac surfaces. If suitable, follow the manufacturer's instructions closely regarding handling safety, dilution, and application method.

Northstone (NI) Limited, Quarry & Asphalt Division, can not be responsible for any damage to any materials supplied, and/or surfaces laid, due to the non-observance of the conditions and precautions outlined above.